

KENWOOD

Listen to the Future

NEXEDGE™

NX-200/300

NEXEDGE™ VHF/UHF Digital & FM Portable Radios

NXDN™

FleetSync®
by KENWOOD

● GENERAL FEATURES

- 5 W (136-174 MHz) Models
- 5 W (400-470, 450-520 MHz) Models
- 512 CH-GID / 128 Zones
- 12-Key Keypad Models
- 14 Character Alphanumeric Aliases
- Backlit Dot Matrix LCD
- 3-Digit Sub-Display
- Function/Status LCD Icons
- RSSI Indicator
- Date & 12/24 Hour Time Clock
- Transmit/Busy/Call Alert/Warn LED
- On/Off Volume Knob
- 16-Position Mechanical Selector
- 6 Front PF & Menu Keys
- 2 Side PF Keys
- Emergency/AUX Key
- 500 mW Speaker Audio
- VOX Ready
- Emergency Call Features
- Emergency Man-Down Option
- Special Alert Tone Patterns
- Time Out Timer
- Busy Channel Lockout
- LCD Battery Status Indicator
- Low Battery Alert
- Battery Saver
- Weather-sealed ACC Connector
- MIL-Spec Speaker Mic Options
- KMC-38GPS Speaker Mic Option
- KPG-111D Windows® FPU
- Flash Firmware Upgrading
- Front Panel Test & Tune
- Cloning
- MIL-STD-810 C/D/E/F
- MIL-STD "Driven-Rain"
- IP-54/55 Water & Dust Intrusion
- Easy Option Port
- PC Serial Interface
- Intrinsically Safe Option
- VGS-1 Voice Guide/Storage Option

● DIGITAL – COMMON

- NXDN™ Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Paging Call
- Emergency Call
- All Group Call
- Status Messaging¹
- Remote Stun/Kill¹
- Remote Check¹
- Short & Long Data Messages¹
- GPS Location with Voice¹
- NXDN™ Scrambler Included

● DIGITAL – CONVENTIONAL MODE

- 64 Radio Access Numbers (RAN)
- Individual & Group Selective Call
- Mixed FM/Digital Operation

● DIGITAL – TRUNKING MODE

- Individual Private Call
- Group Call
- Broadcast Call
- Transmission Trunked Mode²
- Message Trunked Mode²
- Call Queuing with Priority²
- Call Queue Pre-emption²
- Late Entry (UID & GID)²
- 4 Priority Monitor ID's²
- Remote Group Add¹
- Multi-Site IP Network Compatible

● SCAN

- Single Zone / Multi-Zone / List Scan
- Dual Priority Scan (Conventional)

● FM MODES – GENERAL

- 25 & 12.5 kHz Channels
- FleetSync®/II
- DTMF Encode / Decode
- Companded Audio
- Voice Inversion Scrambler
- Encryption/ANI Board Control

● FM CONVENTIONAL ZONES

- QT / DQT
- Two-Tone Decode
- Single/Two-Tone Encode
- Call Key 1-6
- Operator Selectable Tone

● FM LTR® TRUNKED ZONES

- Kenwood LTR® Features

● FleetSync®/II (FM)

- PTT ID Digital ANI
- Selective Call & Group Call
- Status Messaging¹
- Emergency Status
- Caller ID Display
- Short Text Messages¹
- Power On/Off Status Messages¹
- Send/Display GPS (KMC-38GPS)¹
- PTT ID & Emergency GPS Reporting¹
- Status Message Block GPS Reporting¹
- VGS-1 GPS Data Storage



KenwoodLandMobileRadio
25 Years

Options

■ KNB-47L

Li-Ion Battery
(1950mAh)



■ KNB-48L

Li-Ion Battery
(2550mAh)

■ KNB-50NC

Ni-MH Battery
(2000mAh) Intrinsicly Safe

■ KSC-32

Tri-Chemistry Rapid
Rate Charger



■ KVC-20L

D.C. Vehicular Charger
for KNB-47L/48L



■ KMC-41M

MIL-STD & IP 54/55
Speaker Microphone



■ KMC-38GPS

GPS Speaker
Microphone



■ KHS-11

Heavy Duty Earphone



■ KEP-1

Heavy Duty Earphone



■ KRA-22/23

VHF/UHF Helical Antenna



■ KRA-26/27

VHF/UHF Whip Antenna



■ KRA-16/17

VHF/UHF Stubby Antenna



■ KRA-25

VHF High Gain Antenna



■ KRA-28

VHF Broad
Band Antenna



■ VGS-1

Voice Guide
& Storage Unit



■ KBH-11

Belt Clip (2.5")



All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Main Specifications

		NX-200	NX-300
GENERAL			
Frequency Range	Type 1 Type 2	136-174 MHz	450-520 MHz 400-470 MHz
Number of Channels			512
Zones			128
Max. Channels per Zone			250
Channel Spacing	Analog Digital	12.5 / 15 / 25 / 30 kHz 6.25 / 12.5 kHz	12.5 / 25 kHz 6.25 / 12.5 kHz
Operating Voltage		7.5V DC ± 20%	
Battery Life (with KNB-48L)	5-5-90 10-10-80	More than 12.5 hours More than 8.5 hours	
Operating Temperature Range		-22° F to +140° F (-30° C to +60° C)	
Frequency Stability		± 2.0 ppm	± 1.0 ppm
Antenna Impedance		50 Ω	
Dimensions (W x H x D)	Projections not included		
	Radio only with KNB-47L with KNB-48L	2.28 x 5.02 x 1.63 in (58 x 127.5 x 41.3 mm) 2.28 x 5.02 x 1.63 in (58 x 127.5 x 41.3 mm) 2.28 x 5.02 x 1.91 in (58 x 127.5 x 48.5 mm)	
Weight (net)	Radio only with KNB-47L with KNB-48L	8.82 oz (250 g) 13.23 oz (375 g) 14.29 oz (405 g)	
FCC ID	Type 1 Type 2	ALH378400	ALH378500 (Pending)
IC Certification	Type 1 Type 2	282D-378400	282D-378500 (Pending)

		NX-200	NX-300
RECEIVER			
Sensitivity	Digital @ 6.25kHz (3% BER) Digital @ 12.5kHz (3% BER) Analog (12 dB SINAD)	0.20 μV 0.25 μV 0.25 μV	
Selectivity	Analog @ 25 kHz Analog @ 12.5 kHz	72 dB 65 dB	
Intermodulation Distortion	Analog	70 dB (±50,100 kHz)	
Spurious Response	Analog	70 dB	
Audio Distortion		Less than 3%	
Audio Output		500 mW / 8 Ω	
TRANSMITTER			
RF Power Output		5 W / 1 W	
Spurious Response		70 dB	
FM Hum & Noise	Analog @ 25 kHz Analog @ 12.5 kHz	45 dB 40 dB	
Audio Distortion		Less than 3%	
Modulation		16K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

Analog measurements made per TIA/EIA 603 and specifications shown are typical. Kenwood reserves the right to change specifications without prior notice or obligation.

FleetSync™ is a registered trademark of Kenwood Corporation.
LTR™ is a registered trademark of Transcript International.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
Windows™ is a registered trademark of Microsoft Corporation.
NXDN™ is a trademark of Kenwood Corporation and Icom Inc.
NEXEDGE™ is a trademark of Kenwood Corporation.

Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV
International Protection Standard				
Dust & Water Protection	IP54			
	IP55			

footnotes from Front:

¹ Requires NX subscriber unit PC Serial Interface compatible software application (e.g. Kenwood AVL & Dispatch Messaging software) or hardware (e.g. console).

² These trunked features are primarily system programming and operational dependent. Priority Monitor also requires NX subscriber settings.

Listen to the Future

Kenwood has always connected with people through sound. Now we want to expand the world of sound in ways that only Kenwood can, listening to our customers and to the pulse of the coming age as we head toward a future of shared discovery, inspiration and enjoyment.

Kenwood U.S.A. Corporation
Communications Sector Headquarters
3970 Johns Creek Court, Suite 100, Suwanee, GA 30024
Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-574

ARLEN J. DYKEMA
President

Communications Specialists Inc.
TWO-WAY RADIO SALES & SERVICE

4138 S. DIVISION AVE.
GRAND RAPIDS, MI 49548
(616) 534-5862



ISO9001 Registered
Communications Equipment Division
Kenwood Corporation
ISO9001 certification

ADS#32708 Printed in USA